

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

SensorTack® Cleaning & Contact Spray

Further trade names

SensorTack® Reinigungs- und Kontaktspray
 SensorTack® Spray de nettoyage et contact
 SensorTack® de limpieza y contacto

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Cleaner

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	PMA/TOOLS AG	
Street:	Siemensring 42	
Place:	D-47877 Willich - Germany	
Telephone:	+49 2154 922230	Telefax: +49 2154 922255
e-mail:	info@pma-tools.de	
Contact person:	Michael Münter	
e-mail:	msds@pma-tools.de	(Please DO NOT use for requesting Safety Data Sheets.)
Internet:	www.pma-tools.de	
Responsible Department:	Laboratory	

1.4. Emergency telephone number:

Telephone number of the company in case of emergencies (24 h):
 +49 (0) 700 / 24 112 112 (PMR)

Emergency information services / official advisory body:
 <UK> National Poisons Information Service (24 h): 0870 600 6266 (UK only)

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No. 1272/2008

Hazard categories:
 Flammable liquid: Flam. Liq. 2
 Serious eye damage/eye irritation: Eye Irrit. 2
 Specific target organ toxicity - single exposure: STOT SE 3
 Hazard Statements:
 Highly flammable liquid and vapour.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

2.2. Label elements
Regulation (EC) No. 1272/2008
Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:


SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 2 of 11

Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			> 50 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove affected person from the danger area and lay down. Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If unconscious place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritation to respiratory tract, Cough, Headache, Dizziness, central nervous system, Unconsciousness. Chemosis. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

4.3. Indication of any immediate medical attention and special treatment needed

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 3 of 11

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.**Unsuitable extinguishing media**

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

In case of fire: Wear self-contained breathing apparatus.

Wear personal protection equipment (refer to section 8).

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Special danger of slipping by leaking/spilling product.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion.

Stop leak if safe to do so. Collect spillage. Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Avoid contact with eyes and skin. Do not eat, drink or smoke when using this product. See information supplied by the manufacturer. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Further information on handling

Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and after work.

Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 4 of 11

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Protect against direct sunlight. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges.
Recommended storage temperature: 15 - 25 °C.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		dermal		319 mg/kg bw/day
Consumer DNEL, long-term		inhalation		89 mg/m ³
Consumer DNEL, long-term		oral		26 mg/kg bw/day
Worker DNEL, long-term		dermal		888 mg/kg bw/day
Worker DNEL, long-term		inhalation		500 mg/m ³

PNEC values

CAS No	Substance	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Environmental compartment		
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/kg
Soil		28 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 5 of 11

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles. (EN 166).

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wear suitable gloves. (EN 374).

Recommended material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: $\geq 0,7$ mm

Breakthrough time (maximum wearing time): INDEX No. 2, > 30 Min. / INDEX No. 6, > 480 Min.

Replace when worn.

Skin protection

Use personal protection equipment.

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. (89/686/EWG).

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (occupational exposure limit value / exceeding exposure limit values). Combination filtering device (EN 14387) Filter type A1 - A3, (brown). Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	Alcohol

	Test method
pH-Value:	not determined
Changes in the physical state	
Melting point:	not determined
Initial boiling point and boiling range:	82 °C
Flash point:	13 °C DIN 51755
Flammability	
Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	not determined
Auto-ignition temperature	
Solid:	not applicable

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 6 of 11

Gas:	not applicable
Decomposition temperature:	not determined
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 55 °C)	310 hPa
Density (at 20 °C):	0,88 g/cm ³
Bulk density:	not applicable
Water solubility: (at 20 °C)	miscible
Solubility in other solvents	
not determined	
Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
Solvent content:	not determined

9.2. Other information

Solid content:	not determined
Conductivity:	not determined
Surface tension:	not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable. Vapours can form explosive mixtures with air.
Oxidising agent.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	5840	Rat	OECD 401
	dermal	LD50 mg/kg	13900	Rabbit	OECD 402
	inhalation (4 h) vapour	LC50	30 mg/l	Rat	OECD 404

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	1400	96 h	Lepomis macrochirus (Bluegill)	
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	2285	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	(>1000 mg/l)			activated sludge	

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	OECD 301E	95 %	21	
	OECD 303A	99,9 %		

12.3. Bioaccumulative potential

OECD 107

according to Regulation (EC) No 1907/2006

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 8 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

12.4. Mobility in soil

Koc 1,1 - Data obtained by expert judgement.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Recommendation: EAK 140603

Waste disposal number of waste from residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3

according to Regulation (EC) No 1907/2006

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 9 of 11

14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 10 of 11

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 75 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,8,9,13,15,16.

Abbreviations and acronyms

ADN: Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road).

ATE: Acute Toxicity Estimate.

AwSV: Anlagenverordnung wassergefährdender Stoffe (Regulation on facilities handling substances dangerous to water).

BGI: Berufsgenossenschaftliche Informationen (trade association information).

CAS: Chemical Abstracts Service.

CEN: Comité Européen de Normalisation European (Committee for Standardization).

CLP: Classification, Labelling and Packaging of substances and mixtures (REGULATION (EC) No 1272/2008).

DIN: Deutsches Institut für Normung (German institute for standardization).

DMEL: Derived Minimum Effect Level.

DNEL: Derived No Effect Level.

EC: European Community.

EC50: Half maximal effective concentration.

ECHA: European Chemicals Agency.

EG: Europäische Gemeinschaft (European Community).

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

EN: European Norms.

GHS: Globally Harmonized System of Classification and Labelling of Chemicals.

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations.

IBC: Intermediate Bulk Container.

IC50 / ErC50: Inhibitory concentration, 50 %.

ICAO-TI: International Civil Aviation Organization - Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Code for Dangerous Goods.

ISO: International Organization for Standardization.

IUPAC: International Union for Pure and Applied Chemistry.

LC50: Lethal concentration, 50 %.

LD50: Lethal dose, 50 %.

log Kow (Pow): Partition coefficient n-octanol/water.

LQ: Limited Quantities.

MARPOL: International Convention for the Prevention of Marine Pollution from Ships.

OECD: Organisation for Economic Co-operation and Development.

PBT: persistent, bioaccumulative and toxic.

SensorTack® Cleaning & Contact Spray

Revision date: 23.08.2019

Page 11 of 11

PNEC: Predicted No Effect Concentration.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006).

RID: Règlement concernant le transport International ferroviaire de marchandises Dangereuses (Regulation concerning the International Carriage of Dangerous Goods by Rail).

SVHC: Substances of Very High Concern.

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

STOT - SE: Specific Target Organ Toxicity - Single Exposure.

TRGS: Technische Regel für Gefahrstoffe (technical guideline for the handling of hazardous materials).

UN: United Nations.

VOC: Volatile organic compounds.

vPvB: very persistent and very bioaccumulative.

WGK: Wassergefährdungsklasse (water hazard class).

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)